



1 Gallon
Product No. 03951
5 Gallons
Product No. 03950

Bulls Eye® High Hide Odorless

Interior Solvent-Based Primer-Sealer Stain Killer

Bulls Eye High Hide Odorless is a high-solids solvent-base primer developed for interior applications in “people sensitive” areas where oil-base performance is required but odor is a concern. This high hiding, stain blocking primer-sealer dries to a bright white, non-yellowing dead flat finish that may be left unpainted on ceilings. Ideal for water & fire damage or sealing nicotine stains in occupied commercial or multi-family properties. The sprayable 350 VOC formula features a state-of-the-art resin system that won’t clog airless sprayers like many odorless primers. And it dries fast and dead flat for easy sanding.

- Oil-base performance when odor is a concern
- Great for occupied areas
- High solids sprayable formula
- Kills stains from water, graffiti, ink, crayon
- Recommended for fire, water or smoke damage
- Non-yellowing, dries flat, sands easily
- Dries in 30 minutes- recoat in 2 hours

Generic Type:

Acrylic, solvent base very low odor interior primer-sealer stain killer.

Recommended for:

Interior

Previously painted drywall, plaster, masonry (stucco, concrete block, poured concrete, brick) and under high pH texture coatings and drywall compounds, wood (pine, fir, cedar, redwood, plywood), metal (aluminum, steel, stainless steel, copper), rigid plastics, glossy laminates & fiberglass. Blocks stains resulting from water & fire damage, seals stains from nicotine, tannin bleed, dark colors, graffiti, most markers, pencil, crayon, lipstick, etc.

Application:

Brush, roller or pad: **Natural bristle or lambskin**

Airless Spray (3/4 GPM pump or larger): **.017” tip @ 2500 psi @ tip**

Conventional Spray: **Do not thin.**

Spray @ 60 – 70 psi

Practical Spread Rate: **300 – 400 sq. ft. per gallon**

Application Conditions: **40° – 90° F / 10% - 85% RH**

Dry Time (75°F/50%RH)

Touch: **1 hour**

Recoat: **2 hours**

Stain sealing: **2 hours**

Adhesion cure: **7 days**

Tinting: **Up to 1 oz Universal Colorant**

Cleanup: **Mineral Spirits**

Solids by Weight: **78.8%**

Solids by Volume: **54.9%**

Density: **13.1 lbs/gal**

Viscosity Range: **85-90 KU**

Theoretical Spread Rate

@ 1 mil DFT: **820 sq. ft. per gal.**

Gloss @ 60°/7 day cure: **1.4**

Enamel holdout: **1.7% gloss change**

Wet adhesion: **Pass 2000 cycles**

Flexibility (7 day cure)

Slight tension

(3/8” Mandrel): **Pass/4A**

Flash Point

(ASTM D3278): **106°F**

MAX VOC: **350 g/L**

Freeze/thaw stable: **Yes**

Limitations:

Not recommended for exterior application, floors, decks or surfaces subject to immersion or prolonged contact with water. These limitations are not to be construed as all inclusive.

