

COVER-STAIN® PRIMER

Advanced Formula Water-Base SEALER • STAIN-KILLER



Product No.

03600

03603

03601

03604

Performance Characteristics

- Interior/exterior
- Dries to hard, flat finish
- Easy flow
- Great adhesion
- Seals most stains
- Sands crisply in 1 hour

Recommended Uses:

Cover Stain WB was developed for professional painters who require a quick dry, hard, flat finish that sands crisply, adheres to almost anything and seals most stains. This unprecedented water-base formulation delivers many great oil base characteristics without requiring special respirators, solvent clean-up, or hazardous disposal.

Cover Stain WB seals new wood on interior surfaces such as trim for more even color and sheen. It sticks to slick surfaces like paneling and glossy paints and hides dark colors. **Cover Stain WB** also seals all types of wood outside – new, weathered, plywood and T1-11. As a stain blocker it hides stains from nicotine, water and smoke damage and seals tannin bleed from cedar.

Brush, roll, or spray then sand ultra-smooth and apply the finish of your choice knowing your base-coat is an advanced sealer providing excellent adhesion, enamel holdout and stain blocking.

Priming – Use on all types of bare, painted surfaces including wood, drywall, cured plaster, concrete, stucco and masonry, aluminum, vinyl, steel, galvanized metal and PVC. Sticks to dense, glossy surfaces without sanding or deglossing.

Sealing – A great sealer for all kinds of porous surfaces. It allows better topcoat coverage and a more even finish. Also a great enamel undercoat that can be sanded in as little as 45 minutes.

Stain Killing – blocks most stains in one coat. Persistent stains may require a second coat.

Surface Preparation – Surfaces should be clean, dry and sound and free of any contamination, mildew, rust or unsound coatings that may interfere with adhesion. If unsure, always wash surface with an appropriate cleaner or solvent (do not use TSP). Spot prime knots and severe stains with **Zinsser B-I-N® Shellac Base Primer-Sealer** before full surface priming with **Cover Stain WB**.

Application – Shake or stir well and apply using a brush, roller or sprayer (follow spray equipment manufacturer's instructions; for airless spraying use .017 tip at 200 – 2500 P.S.I.). If thinning is required add no more than 10 oz. (295 ml) clean water per gallon and apply a second coat of primer. Apply between 50 °F and 90 ° (10 °C and 32 °C), RH <85%. **WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-Approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Tinting – Tint with up to 2 oz. (60 ml) of universal colorant per gallon.

Coverage – Approximately 400 sq. ft. (37m²) per gallon depending on application method and surface porosity.

Dry Time – Touch in 30 minutes; sand in 45 minutes; recoat in 1 hour. Full hardness and scrape resistance in 7 days.

Cleanup – Warm water and liquid detergent. Wipe up splatters before they dry. Follow manufacturer's directions to clean spray equipment.

Limitations – Not recommended for application to floors or decks or to surfaces subject to immersion or prolonged water contact. These limitations are not to be construed as all-inclusive.

Warranty Guarantee - Cover Stain WB will perform as claimed if directions are followed. Directions are as complete as possible but cannot encompass conditions, applications, techniques, and/or surfaces that are beyond our control. If you have a question, check with your dealer or contact Zinsser & Co., Inc., Somerset, NJ. Warranty is limited to replacement or refund value of product actually used, if such product proves defective within two years of manufacture. No other warranty is expressed or implied.

CAUTION! Do not get in eyes. In case of eye contact, flush eyes with plenty of water for at least 15 minutes. Do not take internally. If swallowed call a physician or Poison Control Center. Do not breathe vapors or spray mist. Ensure good cross ventilation during application and drying. If you experience difficulty breathing, eye watering, headache, or dizziness, increase fresh air; wear an appropriate properly fitted (NIOSH approved) respirator; or leave the area to obtain fresh air. Avoid contact with skin and clothing. Wash thoroughly after handling. **WARNING:** This product contains a chemical known to the state of California to cause cancer and birth defects, or other reproductive harm. Keep container closed when not in use. **KEEP OUT OF REACH OF CHILDREN.**

Technical Assistance - Available through local authorized Zinsser dealers. For the dealer nearest you call 732-469-8100 or visit our website at www.zinsser.com.

Typical Physical Properties

Percent Solids, Weight:	56.81%
Percent Solids, Volume:	39.16%
Dry Time @ 75° F/50% RH:	Touch: 30 minutes Recoat: 1 hour
Flash Point (ASTM D3278):	>200° F (>93° C)
VOC:	<100 g/L
Freeze/Thaw Stable:	Yes
Shelf Life:	60 mo @ 75° F (24° C)
Storage/Handling:	Store indoors 40° – 90° F (4° – 32° C)
Temperature Application Range	50° - 90° F

Packaging

<u>Unit Size</u>	<u>Unit Code</u>	<u>Case Pack</u>	<u>Case Weight</u>	<u>Pallet Pack</u>
5 gallon	03600	1	61 lbs.	36 ea.
3 gallon	03603	1	36.4 lbs.	48 ea.
1 gallon	03601	4	50.1 lbs.	45 cs.
1 quart	03604	6	13.3 lbs.	112 cs.

ZINSSER Co., Inc. 173 Belmont Drive Somerset, NJ 08875

CAUTION: Read and carefully follow all information on this technical data bulletin, on the product label, and on the material safety data sheet for this product. To the best of our knowledge the data contained herein are true and accurate at the date of issuance and are subject to change without prior notice. User must contact ZINSSER Co. to verify correctness before specifying or ordering. No guarantee of accuracy is given or implied. We guarantee our products to conform to Zinsser quality control and assume no responsibility for coverage, performance, or injuries from use.