

DRYWALL PRIMER

SEALER FOR NEW DRYWALL Interior Water-Base

- ◆ Great Hide
- ◆ Quick-dry
- ◆ Seals New Drywall
- ◆ Water Clean-up

Recommended Uses:

Zinsser Drywall Primer is ideal for sealing new drywall. It dries quickly with low odor. Zinsser Drywall Primer won't raise the nap on new drywall and seals the surface for painting in just one hour. Apply with any pad, brush, roller or, sprayer. Use to seal in drywall and tape joints. Sands easily for a smooth surface to apply finish paints. Use a high build, high resin content Zinsser Primer Sealer under low-sheen wall paints for maximum holdout.

Surface Preparation:

Drywall should be clean, dry, sound and free of excessive dust, dirt, grime, grease, oil, wax, mildew, wallpaper adhesive or any contamination that might interfere with adhesion. Kill and remove any mildew.

Application:

Shake or stir before using. Brush, roll or spray. Follow spray equipment manufacturer's instructions. Airless spraying - .015" - .017" tip at 2000 - 2500 P.S.I. If thinning is required add no more than 10 oz. of clean water per gallon and apply a second coat of sealer. Apply between 50°F and 90°F, RH <85 %.

Coverage:

Approximately 400 sq. ft. per gallon depending upon application method and surface porosity.

Dry Time:

Approximately 30 minutes to touch, 1 hour to sand and recoat.

Cleanup: Dry Time:

Warm water and liquid detergent. Wipe up splatters before they dry. Follow equipment manufacturer's direction to clean spray equipment.



Product No.

01500

01501

Warranty:

This product will perform as claimed if directions are followed. Directions are as complete as possible but cannot encompass all conditions, applications, techniques and/or surfaces which are beyond our control. If you have a question, check with your dealer or contact Zinsser Co., Inc., Somerset, NJ. Warranty is limited to replacement or refunded value of product actually used if such product proves to be defective within two years of manufacture. No other warranty is expressed or implied.

Technical Assistance - Available through local authorized Zinsser dealers. For the dealer nearest you call 732-469-8100 or visit our website at www.zinsser.com.

Typical Physical Properties:

Solids by weight	45%
Solids by volume	31%
Gloss/Sheen	Flat (60°-3, 85°-5)
Weight/Gallon	10.36 lbs./gal.
Viscosity range	92 - 97 KU
VOC	<100
Flashpoint (Seta flash)	>200° F.
Dry time @ 70° F & 50% RH	1 hour
Shelf Life	60 months @ 75° F.
Storage/Handling	Store indoors 40° F - 90° F (4° - 32° C)

CAUTION! Do not get in eyes. In case of eye contact, flush eyes with plenty of water for at least 15 minutes. Do not take internally. If swallowed call a physician or Poison Control Center. Do not breathe vapors or spray mist. Ensure good cross ventilation during application and drying. If you experience difficulty breathing, eye watering, headache, or dizziness, increase fresh air; wear an appropriate properly fitted (NIOSH approved) respirator; or leave the area to obtain fresh air. Avoid contact with skin and clothing. Wash thoroughly after handling. **WARNING:** This product contains a chemical known to the state of California to cause cancer and birth defects, or other reproductive harm. Keep container closed when not in use. **KEEP OUT OF REACH OF CHILDREN.**

Packaging

Unit Size	Unit Code	Case Pack	Case Weight	Pallet Pack
5 gallon	01500	1	61 lbs.	36 ea.
1 gallon	01501	4	50.1 lbs.	45 cs.

ZINSSER Co., Inc. 173 Belmont Drive Somerset, NJ 08875

CAUTION: Read and carefully follow all information on this technical data bulletin, on the product label, and on the material safety data sheet for this product. To the best of our knowledge the data contained herein are true and accurate at the date of issuance and are subject to change without prior notice. User must contact *ZINSSER Co.* to verify correctness before specifying or ordering. No guarantee of accuracy is given or implied. We guarantee our products to conform to Zinsser quality control and assume no responsibility for coverage, performance, or injuries from use.